



SPITWATER[®]
INDUSTRIAL CLEANING & HEATING EQUIPMENT



PROUDLY AUSTRALIAN MADE

Pictures showing optional wall-mount brackets (left) and manual hose reel (below)



SPITWATER[®]
INDUSTRIAL CLEANING & HEATING EQUIPMENT

HT11-110E GT - HI-TEMP PRESSURE CLEANER

SPECIFICATIONS

1650 psi (110 Bar) Pump Pressure
 2700 psi Turbo Pressure (Optional)
 11 Litres per minute Pump Volume
 240 Volt 3 hp Electric Motor
 15 Amp Plug
 1450 rpm Industrial Machine
 Delayed Total Stop protection
 Inlet Water Temperature Sensor
Accepts Water up to 80° C

STANDARD EQUIPMENT

Galvanised Base & Stainless Steel Cover
 Chemical Injector with 2 m Hose & Filter
 10 Metres of High Pressure Hose
 Insulated On/Off Pistol Assembly
 Dual Lance Assembly with Hi-Lo Valve
 Operators Manual

OPTIONAL EQUIPMENT

Galvanised Wall Mounting Brackets
 Galvanised Floor Mounting Brackets
 Manual or Retractable Hose Reels

<u>FEATURES</u>		<u>BENEFITS</u>
Interpump with Ceramic Pistons and Brass Head, 1450RPM Low Speed	➔	Longer pump life, non-corrosive pump head
Delayed Total Stop	➔	Reduces maintenance costs
Inlet Water Filter	➔	Protects the pump from overheating in bypass
Pressure Gauge	➔	Stops debris from scoring pistons and seals
	➔	Easily monitors pump performance

Phone: 1800 172 005
www.spitwater.com.au